



Architectural Panel Systems Australia  
 6 Kambouris Crt,  
 Corio, VIC, 3214  
 E | info@apsaus.com.au  
 W | www.apsaus.com.au  
 M | 0432 590 125  
 P | 03 5274 9600

Material Selection	Std. Panel Width	Thickness	L/M Per M2	Weight Per M2 (Panels Only)	Clips Per M2	Screws Per M2
<b>Copper</b>	225mm	0.7mm	4.45	8.4	15	30
	335mm	0.7mm	2.98	7.49	10	20
	525mm	0.9mm	1.91	9.25	7	14
<b>Zinc</b>	255mm	0.7mm	4.45	7.53	15	30
	425mm	0.7mm	2.36	5.99	8	16
<b>Stainless Steel</b>	225mm	0.55mm	4.45	6.18	15	30
	335mm	0.55mm	2.98	5.52	10	20
	525mm	0.7mm	1.91	6.67	7	14
<b>Aluminium</b>	225mm	0.8mm	4.45	2.9	15	30
	335mm	0.8mm	2.98	2.59	10	20
	525mm	1.0mm	1.91	3.11	7	14
<b>Brass</b>	255mm	0.6mm	3.93	6.35	13	26
	425mm	0.8mm	2.36	8.37	8	16
<b>Bronze</b>	225mm	0.6mm	4.45	7.19	15	30
<b>Corten</b>	225mm	0.7mm	4.45	7.68	15	30
	335mm	0.7mm	2.98	8.56	10	20
	525mm	0.7mm	1.91	6.59	7	14
<b>Colorbond Metallic</b>	225mm	0.55mm	4.45	6.08	15	30
	335mm	0.55mm	2.98	5.43	10	20
	525mm	0.55mm	1.91	5.22	7	14
<b>Colorbond Ultra</b>	225mm	0.55mm	4.45	6.08	15	30
	335mm	0.55mm	2.98	5.43	10	20

<b>Colorbond</b>	525mm	0.55mm	1.91	5.22	7	14
	225mm	0.55mm	4.45	6.08	15	30
	335mm	0.55mm	2.98	5.43	10	20
<b>Zincalume</b>	525mm	0.55mm	1.91	5.22	7	14
	225mm	0.55mm	4.45	6.03	15	30
	335mm	0.55mm	2.98	5.38	10	20
<b>Galvanised</b>	525mm	0.75mm	1.91	6.99	7	14
	225mm	0.55mm	4.45	6.28	15	30
	335mm	0.55mm	2.98	5.61	10	20
<b>Perforated</b>	525mm	0.75mm	1.91	7.26	7	14
	225mm	TBC	4.45	-	15	30
	335mm	TBC	2.98	-	10	20
	525mm	TBC	1.91	-	7	14

\*All information provided above is to be used as a guide and is a recommendation only.

\*Panel width, thickness, foam, batten spacings and stop ends can be changed accordingly to suit individual project needs.

\*All Panel widths listed are standard sizes only, panels can be rolled into any width required for specific projects.

\*Panel weights listed are approximate only.